





Depósito CHL

CÓDIGO		A610055	A610062	A610067	A610070	A610074	A610080
Capacidad (L)		500	1.000	1.500	2.000	3.000	5.000
Ø	Diámetro (mm)	850	1100	1250	1400	1550	1820
H	Alto (mm)	900	1155	1305	1455	1605	1875
L	Largo (mm)	980	1150	1350	1430	1750	2080
A	Ancho pletina inferior (mm)	170	270	270	270	270	270
B	Alto pletina inferior (mm)	85	145	135	135	155	160
C	Distancia conectores inferiores (mm)	80	140	140	140	140	140
D	Alto conectores inferiores (mm)	45	65	65	65	65	65
E	Ancho pletina superior (mm)	170	270	270	270	270	270
F	Alto pletina superior (mm)	80	135	135	135	155	160
G	Distancia conectores superiores (mm)	80	140	140	140	140	140
I	Alto conectores superiores (mm)	755	980	1130	1280	1430	1700
DN1	Diámetro tapa superior (mm)	300	400	400	400	400	400
DN2	Rebosadero	1"	1"1/4	1"1/2	1"1/2	1"1/2	2"
DN3	Conexión flotador (mm)	28	28	28	28	28	28
DN4	Salida agua	1"	1"1/4	1"1/2	1"1/2	1"1/2	2"
DN5	Salida vaciado completo	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Peso (Kg)		17	23	39	49	76	121

Los depósitos CHL son conformes al Reglamento UE 10/2011 de 14/01/2011 y al Reglamento CE 1935/2004 de 27/10/2004